

AMC FX5

AMC main board with Virtex 5 FXT FPGA



Description

The AMC FX5 is a main board for AMC MicroTCA or ATCA that provides powerful DMA, memory, and other resources to a mezzanine board. It supports 1GbE, PCIe, or 10GbE.

Two front-panel ports support 1000 BASE-T, and two AMC ports (0 and 1) support 1000 BASE-X. AMC ports 4-11 (the fat pipes region) can support either PCI Express or ethernet.

Signals connected to the mezzanine board include 44 LVCMOS (2.5v) single-ended; 40 LVDS pairs; and 4 full-duplex RocketIO channels.

In addition, the board has 1 GB DRAM (DDR2 SODIMM); a crystal oscillator (XCO), user-programmable from 10 to 215 MHz; and a Xilinx Virtex 5 FPGA (XC5VFX70T or optional 100T) with PowerPC 440 CPU. Programmable FPGA resources are provided through the mezzanine board.

A time code input (1 pps or IRIG-B) also is provided.

EDT provides FPGA configuration files. Custom configuration files can be requested.

Features

Main board (AMC uTCA / ATCA) - provides DMA, memory, and other resources to a mezzanine board, which provides programmable FPGA resources

Interfaces:

- Front panel = two 1000 BASE-T
- AMC connector = two 1000 BASE-X, plus fat pipes region (configurable for PCIe or ethernet)

Signals connected to mezzanine board:

- 44 LVCMOS (2.5v) single-ended signals
- 40 LVDS signal pairs
- 4 full-duplex RocketIO channels

DRAM: 1 GB DDR2 SODIMM

XCO: One user-programmable (10-215 MHz)

Time code: 1 pps, IRIG-B, or other input

Applications

EDT mezzanine board support for UTCA / ATCA form factors

Specifications

Product Type	AMC main board for uTCA or ATCA; it supplies DMA, memory, and other resources to a mezzanine board.	
FPGA Resources	One non-programmable Xilinx Virtex 5 FXT FPGA (XC5VFX70T or optional 100T) with PowerPC 440 CPU. Programmable FPGA resources are available on the corresponding mezzanine board.	
Memory	DRAM (200-pin SODIMM DDR2)	1 GB
Clocks	One programmable XCO	10-215 MHz
Data Rates	Dependent on such factors as data format, mezzanine board, and system variables:	
	1GbE	200 MB/s
	PCI Express	700 MB/s
	10GbE	TBD
Data Format (I/O)	Time code (from external receiver)	1 pps, IRIG-B, or other input, with user-configurable output
	Other data (depending on mezzanine board used)	1 GbE (front and back) or PCIe (back) or 10GbE
Compliance	PICMG AMC.0 R2.0	
Connectors	One 7-pin Lemo for time code Two RJ45 One 6-pin .100" x 1 row square .025" Two 2-pin .100" x 1 row square .025" One SEAF connector to mezzanine board	1 pps, IRIG-B, or other input, with user-configurable output 1000 BASE-T For FPGA JTAG (IEEE 1149.1) For RS232 UART Mate to SAMTEC SEAM-30-11.0-S-08-2-A: - 44 LVCMOS (2.5v) single-ended signals - 40 LVDS signal pairs - 4 full-duplex RocketIOm channels
Cabling	Consult EDT for purchase options.	
Physical	This single-width main board pairs with a mezzanine board, so total weight and height are dependent on the mezzanine board used.	
	Weight	With mezzanine board: 8.6 oz.
	Dimensions	With mezzanine board: 7.25 x 2.875 x 1.25 in.
Environmental	Temperature (operating / non-operating)	0° to 40° C / -40° to 70° C
	Humidity (operating / non-operating)	1% to 90%, non-condensing at 40° C / 95%, non-condensing at 45° C
System and Software	System must have a PCI Express bus (1 or 4 lanes). Software is included for Windows and Linux; for versions, see www.edt.com .	

Ordering Options

- Mezzanine board: DRX or OCM2.7G
- Data format: 1GbE / PCIe / 10GbE (dependent on mezzanine board)
- FPGA: XC5VFX**70T** / 100T

Bold is default. For more options, see mezzanine board detail. **Ask** about custom options.

International Distributors



Sky Blue Microsystems GmbH
Geisenhausenerstr. 18
81379 Munich, Germany
+49 89 780 2970, info@skyblue.de
www.skyblue.de



In Great Britain:
Zerif Technologies Ltd.
Winnington House, 2 Woodberry Grove
Finchley, London N12 0DR
+44 115 855 7883, info@zerif.co.uk
www.zerif.co.uk