

Nallatech's 385A low profile accelerator card provides a powerful PCI-Express computing and I/O platform for FPGA development and deployment across a range of application areas including High Performance Computing, Image Processing and Network Analytics.

- Featuring Arria 10 FPGA
 Up to 1.5 TFLOPS of processing power
- Two high bandwidth banks of DDR3 SDRAM memory
- 8-lane PCIe Gen 3.0 card
- Two 10 & 40GbE Network Ports

Designed to address a range of computeintensive and latency-critical applications

- Compute, Network & Storage
- Finance and Risk Analysis
- Datacenter
- High Performance Computing
- Communications (Wireless and Wireline)
- Industrial, Broadcast, Embedded
- Medical
- Automotive



The Industry's first floating point-enabled FPGA card with OpenCL tool flow



OpenCL



» Intel FPGA OpenCL Software Development Kit (SDK)

- Abstraction enables faster and higher-level software development flow
- Emulate OpenCL application code on x86 platforms in seconds
- Push button flow generates FPGA executable, driver and API
- Add optimized HDL IP cores to OpenCL designs as libraries

» Hardware Description Language (HDL)

- Traditional VHDL/Verilog tool flow support
- Aimed at hardware-orientated customers
- Hand-code HDL for ultimate performance
- FPGA card designed to support standard Intel IP cores for Arria 10

Nallatech 385A FPGA Accelerator Card

Form Factor

- » Half-height, half-length, single width PCI Express card
- » 167.6mm x 68.9 mm x 17mm

Host Interface

- » 8-lane PCI-Express Gen 3.0
- » Actual performance is host computer chipset and operating system dependent

Processing

- » Intel Arria-10 F1517 NF40 package
- » Default configuration: GX 1150
- » Core speed grade -2, I/O speed grade -3
- » Contact Sky Blue and Zerif for other FPGA options

DDR4 SDRAM Memory

- » Two banks of DDR3 SDRAM x 72 bits
- » 4GB per bank (8GB total / 16GB & 32GB version also available)
- » 2133MT/s per bank

Application Development

» Supports multiple design flows including Intel FPGA OpenCL SDK and HDL

<u>Electrical</u>

- » On-card power derived from the host motherboard PCIe slot
- » Power dissipation is application dependent
- » Typical power consumption $\sim\!30W$
- » Card designed to deliver up to 75W power consumption


<u>Quality</u>

- » Manufactured to ISO9001:2008 IPC-A-610-Class III
- » RoHS compliant

Power Supply Monitoring & Reporting

- » On-board Intel USB-Blaster II
- » Power and temperature monitoring*

Customization: Technical specifications (e.g. FPGA type, size, external memory capacity etc.) can be modified to meet the exact needs of commercial customer applications as off-the-shelf product available to the general market.



Two 10/40G QSFP Network Ports

- » Flexible low jitter clocking supports multiple telecom standards - 10/40GbE, Fiber Channel
- » Each QSFP can be independently clocked
- » Network recovered with jitter attenuation (optional)
- » QSFP clocking: user programmable, or CPRI, 1GbE (optional)
- » Others: external clock input, 1PPS input (optional)

Cooling

- » Standard: single-width active heatsink (embedded fan)
- » Optional: single-width passive heatsink

Environmental

- » Cooling: Air convection
- » Operating temperature: 0°C to 35°C

<u>Deliverables</u>

- » 385A FPGA card
- » USB cable (back panel access)
- » Built-In-Self-Test (BIST)
- » OpenCL "HPC" Board Support Package (BSP)*
- » 1-year access to online support lounge
- » 1-year hardware warranty

Application optimization: Nallatech provides consultancy services assisting customers in the porting, optimization and benchmarking of applications executed on Nallatech FPGA accelerators.

* Please check with Sky Blue or Zerif for availability V2-5a: 2017/10/02

International Distributors



Sky Blue Microsystems GmbH Geisenhausenerstr. 18 81379 Munich, Germany +49 89 780 2970, info@skyblue.de www.skyblue.de



In Great Britain:
Zerif Technologies Ltd.
Winnington House, 2 Woodberry Grove
Finchley, London N12 0DR
+44 115 855 7883, info@zerif.co.uk
www.zerif.co.uk