

BittWare
a **molex** company

TeraBox 1411B
1U FPGA Server

High Density Standard-Depth FPGA Server with Removable Storage

At the extreme of FPGA server density, the TeraBox 1411B gives the highest level of compute and network capability in a 1U chassis as well as removable storage. This server can support up to two of our largest Achronix Speedster7t, Intel Stratix 10, Xilinx UltraScale+, or Intel Agilix FPGAs.

This innovative product supports PCIe Gen4 and up to 4 NVMe Gen4 U.2 drives and features an AMD EPYC processor in a standard rack depth chassis.

AMD
EPYC




key features

Up to
8 QSFP-DDs
for 16x 100G or
64x 10/25G

Up to **120TB**
of PCIe 4.0
removable
storage

Standard Height
Double Slot
Support for BittWare's full
range of FPGA cards



* Option 1: NVMe to Motherboard
** Option 2: NVMe to FPGA Card

chassis key specs

1U depth, 28.25 in (71.75 cm)

Processor: (1) AMD EPYC 7002 Series Processor (1401B)

Ethernet: 2x RJ45 10G base-T by Intel® X550-AT2, 1x RJ45 Dedicated IPMI LAN port by RTL8211E

Memory: 8x DDR4 DIMMs

Storage: 2x M.2 drives, 4x Removable U.2 NVMe drives

Slots: 2x front panel PCIe Gen4 x16

Power supply: 1+1 AC 1300W, 110/220V

NVMe-to-Motherboard:

1-2 FPGA cards connected directly to the Motherboard (PCIe Gen4 x16)

(4) drives connected directly to the motherboard

Up to a total of 120TB

NVMe-to-FPGA Card:

1-2 FPGA cards connected directly to the Motherboard (PCIe Gen4 x16)

(2) drives connected directly to each FPGA card via OCuLink

Up to a total of 120TB

Requires 3rd party IP

TeraBox 1411B

1U FPGA Server

BittWare FPGA Cards

The TeraBox 1411B supports up to two dual-slot BittWare PCIe FPGA cards. Choose from a variety of cards based on Achronix, Intel, and Xilinx FPGAs. System specs will vary greatly, depending on the FPGA card you select. For example, with two BittWare UltraScale+ PCIe cards, which support up to 512 Gbytes of DDR4 per card, the chassis can support as much as 1 Terabyte of DDR4 on the FPGA cards in 8 banks. With two Agilex cards using breakout cables, each chassis supports 12x 100GbE.

Certified Cards

The TeraBox 1411B supports many of BittWare's Achronix, Intel or Xilinx FPGA-based PCIe cards. The table below lists specifications for some of our certified cards*:

	FPGA	Cards per Server	Memory	Front Panel System I/O	Processing
S7t-VG6	Achronix Speedster7t	2	<ul style="list-style-type: none">4 banks GDDR6 (up to 16 GBytes)	<ul style="list-style-type: none">1x QSFP-DD, 1x QSFP6x 100/50/40/25/10 GbE	<ul style="list-style-type: none">692K 6-input lookup tables (LUTs)375 Mbits embedded RAM
IA-840F	Agilex AGF027	2	<ul style="list-style-type: none">4 banks DDR4 (up to 128 GBytes)	<ul style="list-style-type: none">3x QSFP-DDs6x 100 GbE, or 24x 25/10 GbE	<ul style="list-style-type: none">2.6 million system logic elementsUp to 8,528 DSP blocks
IA-420F	Agilex AGF014	2	<ul style="list-style-type: none">2 banks DDR4 (up to 32GBytes)	<ul style="list-style-type: none">1x QSFP-DD2x 100 GbE, or 8x 25/10GbE	<ul style="list-style-type: none">1.4 million system logic elementsUp to 4,510 DSP blocks
XUP-VV8	UltraScale+ VU13P	2	<ul style="list-style-type: none">4 banks DDR4 (up to 512 GBytes)8 banks QDRII+ (up to 2.3 Gbits)	<ul style="list-style-type: none">4x QSFP-DDs8x 100/50/40/25/10 GbE	<ul style="list-style-type: none">3.8 million system logic cellsUp to 12,288 DSP slices

*Subject to availability. Contact BittWare for additional FPGA card options.



Server Configurations

Low

- (1) AMD EPYC 7232P (3.1GHz, 8C/16T) Processor
- 64GB DDR4
- (2) 1 TB M.2 (RAID1)
- (1+1) 1300W Power Supplies

Medium

- (1) AMD EPYC 7302P (3.0GHz, 16C/32T) Processor
- 128GB DDR4
- (2) 1TB M.2 (RAID1)
- (1+1) 1300W Power Supplies

High

- (1) AMD EPYC 7502P (2.5GHz, 32C/64T) Processors
- 256GB DDR4
- (2) 1TB M.2 (RAID1)
- (1+1) 1300W Power Supplies

Premium

- (1) AMD EPYC 7702P (2.0GHz, 64C/128T) Processor
- 512GB DDR4
- (2) 1TB M.2 (RAID1)
- (1+1) 1300W Power Supplies

Ultra

- (1) AMD EPYC 7702P (2.0GHz, 64C/128T) Processor
- 1TB DDR4
- (2) 1TB M.2 (RAID1)
- (1+1) 1300W Power Supplies

Rev 2022.5.25 | May 2022

International Distributors



Sky Blue Microsystems GmbH
Geisenhausenerstr. 18
81379 Munich, Germany
+49 89 780 2970, info@skyblue.de
www.skyblue.de



In Great Britain:
Zerif Technologies Ltd.
Winnington House, 2 Woodberry Grove
Finchley, London N12 0DR
+44 115 855 7883, info@zerif.co.uk
www.zerif.co.uk

The TeraBox Advantage

Choosing a TeraBox FPGA server means knowing you are getting a pre-configured and tested solution. This includes setup and installation of your FPGA cards and associated hardware, your choice of operating system, and development tools. Your TeraBox arrives ready for use—giving your team more time for development and deployment.