

# PCIe8g3 KU-10G

PCIe Gen3 x8 board: Kintex Ultrascale FPGA and 10G SFP/+s



Includes active FPGA heat sink (not shown).

## Description

The PCIe8g3 KU-10G is a fast, versatile PCI Express (PCIe, Gen3) x8 interface with up to four 10G SFP/+ ports. It supports 1/10GbE, OC3/12/48/192 (STM1/4/16/64), or OTU1/2/2e/2f.

Each port links to the user-interface (UI) FPGA for serialization / deserialization (SERDES) and clock recovery. Each port has its own reference clock, programmable for 10–210 MHz.

The UI FPGA is a Xilinx Kintex Ultrascale (U035, 060, 085, or 115) with access to two independent 64-bit wide blocks (2 GB each, 4 GB total) of DDR3 DRAM which can act as data buffers. This UI FPGA configures from flash at power-on, and can be reconfigured as many times as desired without powercycling. Up to five images are available, depending on which UI FPGA model is used.

The PCIe FPGA provides up to 16 independent DMA channels via EDT FPGA configuration files.

An optional Lemo supports time code input (1 pps or IRIG-B), with user-configurable output and two cabling options.

EDT provides FPGA configuration files to support 1GbE and 10GbE at the PHY layer; OC3/12/48/192 and OTU1/2/2e/2f (raw, framed, framed and descrambled); and demultiplexing. Custom files can be requested.

## Features

PCIe (Gen3) x8 interface with up to four 10G SFP/+s

Data formats: 1/10GbE, OC3/12/48/192 (STM1/4/16/64), OTU1/2/2e/2f

FPGA (UI): One user-configurable Xilinx Kintex Ultrascale (035, 060, 085, 115)

FPGA (PCIe): One (up to 16 DMA channels via EDT FPGA configuration files)

DRAM (DDR3): Two independent 64-bit blocks of 2 GB each (4 GB total)

EDT intellectual property for 10GbE PCS and PMA layers, SONET/SDH framing, demultiplexing, and G.709 framing

Optional Lemo for time code input, with user-configurable output

## Applications

Telecommunications monitoring, recording, and processing

SONET/SDH to ethernet conversion

Multiple other network processing applications

