

RCX C-Link

Remote camera extender for Camera Link over fiberoptic



Description

The RCX C-Link is a remote camera extender for Camera Link over fiberoptic cable. The camera can be tens, hundreds, or thousands of meters from the host, depending on the transceiver.

The extender, similar in size to a Camera Link cable connector, attaches directly to the MDR26 connector on the back of the camera. A fiberoptic cable then attaches to an SFF or SFP transceiver on the back of the module.

Triggering / serial is provided via Camera Link, or externally via an optional Lemo power connector. The Lemo can be used either for triggering and single serial, or for dual serial (one via Camera Link and one via an independent port). It also can be used for resync (required for full mode).

Module pairs can be used to create a long-range fiberoptic connection to an EDT or third-party Camera Link framegrabber. Alternatively, an EDT direct-from-fiber (FOX) framegrabber can be used, eliminating the need for modules at the computer end.

Line and frame triggering are supported over camera control lines, and all camera modes (base, dual base, medium, full, extended) are supported.

Features

- Extender adapts Camera Link data to a fiberoptic interface
- Attaches to the device's MDR26 connector, replacing Camera Link cables
- Can join with a second module to form a fiberoptic extension cord
- Allows remote operation – camera can be tens, hundreds, or thousands of meters from the host computer, depending upon transceivers
- Provides electrical isolation of camera from host
- Supports line & frame triggering over camera control (CC) lines
- Provides an optional Lemo power connector for more options (external triggering, single or dual serial, full-mode resync)
- Supports data rates up to 240 MB/s (base mode) or up to 750 MB/s (full mode)
- Can connect directly to an EDT FOX board

Applications

- Astronomy / biology / microscopy
- Aerial mapping / traffic systems
- Commercial film / multimedia
- Medical and nuclear imaging
- Remote scientific monitoring
- Manufacturing / inspection
- Machine vision / robotics
- Security / surveillance
- Scanning / archiving

Specifications

Product Type	RCX C-Link is a remote camera extender for Camera Link to fiberoptic cable.		
Memory	FIFOs for up to several lines of data; no frame memory		
Data Rates	Fiber operates at 1.25 or 2.5 Gb/s, passing video data at up to 120 or 240 MB/s for base mode, or up to 750 MB/s for full mode		
Data Format (I/O)	Camera Link		
Camera Link Compliance	Modes	Base, dual base, medium, full, extended full – common configurations NOTE: All modes except base mode require specially configured module pairs.	
	Pixel clock rate	20–80 MHz; for extended full mode, up to 72 MHz maximum	
	Serial	9600 to 115,200 baud	
	Control	CC1 - CC4	
	Connector	One MDR26	
EU Compliance	CE	EMC directive 2004/108/EC and low voltage directive 73/23/EEC	
	RoHS	Contact EDT	
	WEEE	WEEE directive 2002/96/EC	
Laser Safety	Class 1 (for EDT-supplied transceivers)		
Noise	0 dB		
Transceiver	One fiberoptic SFF or optional SFP (duplex LC, CWDM, or bidirectional), In duplex LCs, available wavelengths and cables include:		
	Wavelength	Cable	Range at 1.25 Gb/s
	850 nm	62- μ MMF	300 meters
	850 nm	50- μ MMF	500 meters
	1310 nm	9- μ SMF	10 kilometers
			Range at 2.5 Gb/s
			150 meters
			250 meters
			5 kilometers
	For longer ranges (10 to 100+ kilometers): CWDM and bidirectional SFFs or SFPs are available in various wavelengths; contact EDT.		
Triggering / Serial	Via Camera Link, or externally via optional 7-pin Lemo power connector		
Power	Consumption	Less than 3 W at 4.75 to 18 V DC	
	Supply	4.75 to 18 V DC	
	Connector (standard)	2-conductor Switchcraft 712RA; mate to Switchcraft 760K	
	Connector (optional)*	7-pin Lemo ECG.0B.307.CLV; mate to FGG.0B.307.CLAD.56	
	* The optional Lemo connector provides external control either for triggering and single serial, or for dual serial (one via Camera Link and one via an independent port). It also provides resync (required for full mode framegrabber-end modules).		
Cabling	Cabling is purchased separately; consult EDT for options.		
	Fiber connection polish	Standard physical contact (PC)	
	Camera Link adapter	Can be used if obstacles prevent the module from plugging into the camera	
	Resync (medium or full mode only)	40 MHz for camera input of 20 to 40 MHz 66.6 MHz for camera input of 41 to 66.6 MHz 80 MHz for camera input of 66.7 to 80 MHz	
Physical	Weight	4 oz. typical	
	Dimensions	2.4 x 1.6 x 0.75 in. (requires an additional 2.2 in. for a 90° bend for the LC)	
Environmental	Temperature (operating / non-operating)	10° to 40° C (extended -40° to 60° C) / -40° to 60° C	
	Humidity (operating / non-operating)	20% to 80%, non-condensing at 40° C / 95%, non-condensing at 40° C	
System and Software	Computer system requirements are framegrabber-dependent; for details, see the user's guide for your framegrabber. Software for updating VisionLink RCX firmware using an EDT framegrabber is included with EDT framegrabber products.		

Ordering Options

- Mode: **Base** / medium / full / extended
 - Transceiver: [see options above]
 - Power – supply (AC input): **110** / 220 V
 - Power – connector: **Switchcraft** / Lemo
 - Cabling: See options above
 - Environmental: Extended temperature
- Bold is default. Ask about custom options.**

Contact



Sky Blue Microsystems GmbH
Geisenhausenerstr. 18
81379 Munich, Germany
+49 89 780 2970, info@skyblue.de
www.skyblue.de



In Great Britain:
Zerif Technologies Ltd.
H5 Ash Tree Court
Nottingham NG8 6PY, England
+44 115 855 7883, info@zerif.co.uk
www.zerif.co.uk