

Single-Mode Triplex Window Couplers

Features

- Long-haul telecommunications
- CATV systems & Fiber sensors
- Local area network
- Splits optical signal for routing to multiple devices or inputs
- multimode fused optical splitter
- Low excess loss
- Various coupling ratio
- Compact size



Description

The **Single-Mode-LC Fiber Optic Splitter Cable** is a fused passive splitter that offers a handy solution to split optical signal for routing to multiple devices, inputs, or patch panels. This 1x2 splitter cable provides a 100 to 50/50 split and is designed to operate with 1310 and/or 1550nm.

Performance Specifications	
Coupling Ratio(%)	1-50
Directivity (dB)	>55 dB
Operating Temperature	-20 ° C - 85 ° C
Storage Temperature	-40 ° C - 85 ° C
Fiber Type	Corning Singlemode SMF-28 , DS Fiber, or Flexcore
Fiber Pigtail Length (m)	1meter
Port Configuration	1x2 or 2x2
Package Dimension	Package A, B, C

Single mode Triplex Window Wideband Couplers	
Grade	P
Excess Loss (Typical)(dB)	0.10
Maximum Insertion loss (dB)	3.6
Uniformity (Max.) (dB)	0.7
Polarization Sensitivity (dB)	0.10
Operating Wavelength (nm)	1310 /1550 +40, and 1490+ 10

Coupling Ratio/Insertion Loss Conversion Chart

Coupling Ratio	Insertion Loss
	Premium
40/60	4.4/2.5
30/70	5.65/1.8
20/80	7.5/1.2
10/90	10.8/0.65
5/95	13.9/0.4
1/99	21/0.2

Package Dimensions and Pigtail Style

Package Dimensions	
Package A	3mm x 54mm stainless steel tube
Package B	3mm x 60mm stainless steel tube
Package C	90mm x 20mm x 10mm ABS
Pigtail Style	
Package A	250um bare fiber
Package B	250um bare fiber or 900um loose tube
Package C	3mm cable or 900um loose tube

Ordering Information

Type	Grade	Wavelength	Coupling Ratio (dB)	Port	Package	Pigtail Style	Fiber Type	In/Out Connector
S*	P	35=1310/1550nm	50=50/50	0102=1x2	A=Package A	1=Bare Fiber	0=SMF-28	0=None
W*	A	36=1310/1585nm	30=30/70	0202=2x2	B=Package B	2=900µm Jacket	D=DS Fiber	1=FC/APC
			10=10/90		C=Package C	3=3mm Cable		2=FC/PC
			05=5/95					3=SC/APC
			01=1/99					4=SC/PC
								5=ST
								6=LC

* S – Single Mode Standard Coupler

* W – Single Mode Wideband Coupler

All statements, technical information, and recommendations related to the products herein are based upon information believed to be reliable or accurate. However, the accuracy or completeness thereof is not guaranteed, and no responsibility is assumed for any inaccuracies. Please contact Sky Blue or Zerif Instruments for more information.

Contact